

airpixel.cz

AIR Commander
ENTIRE

Z-CAM E2 Control

USER'S MANUAL

Before using this product, carefully read all product documentation and retain it for future reference.

Connection

Thanks for choosing Entire for Z-CAM E2 series camera control! Connection is very easy and takes just few minutes.

WiFi control*:

- a. Open the Entire's MENU and configure control mode to "WiFi"
- b. Open WiFi connection and scan for the Z-Cam E2 network. Click to connect.
- c. Default WiFi password of the camera is 12345678
- d. Once connected, Entire's STATUS LED will go green and you are ready to go.

. * WiFi control of the Z-Cam E2 is not available at flag ship series, where only 5.8GHz WiFi is available.

USB control:

This feature is available for all the E2 series.

- a. Open the camera MENU and configure USB mode to "network"
- b. Open the Entire's MENU and configure control mode to "LAN"
- c. Connect the camera by USB-C cable or via USB-C adaptor for the Entire rev1.
- d. Once connected, Entire's STATUS LED will go green and you are ready to go.

Warranty

All warranty and post-warranty service provides manufacturer at www.airpixel.cz. If any malfunction or non-usual behavior occur, stop using device and contact manufacturer at info@airpixel.cz.

Manufacturer

AIRPIXEL.CZ

Ing. Ilja Mašík Ph.D.

Na výsluní 25

Prague 10

100 00

Czech Republic

Made in Czech Republic